## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

## **Listing of Claims:**

1

2

3

4

5

1

2

3

1

2

3

1

2

3

1

2

- 1. (Currently Amended) A fire-resistant flexible wall (1) having a first surface (3) designed to be presented to a fire area (10) and a second surface (4) on the opposite side from the first surface (3), wherein the said wall being characterized in that it incorporates includes a flexible insulating material layer (6) between a first basalt fiber fabric layer (5) and the second surface (4).
- 2. (Currently Amended) The fire-resistant flexible wall [[(1)]] as claimed in claim 1, characterized in that it incorporates further including a second basalt fiber fabric layer [[(7)]] between the flexible insulating material layer [[(6)]] and the second surface [[(4)]].
- 3. (Currently Amended) The fire-resistant flexible wall [[(1)]] as claimed in any one of the preceding claims, characterized in that claim 1, wherein the first [[(5)]] basalt fiber fabric layer and the flexible insulating material layer [[(6)]] are joined together by stitching.
- 4. (Currently Amended) The fire-resistant flexible wall [[(1)]] as claimed in claim 2, characterized in that wherein the second [[(7)]] basalt fabric layer and the flexible insulating material layer [[(6)]] are joined together by stitching.
- 5. (Currently Amended) The fire-resistant flexible wall [[(1)]] as claimed in claim 3 or 4, characterized in that wherein the stitching is done with basalt yarn.
- 6. (Currently Amended) The fire-resistant flexible wall [[(1)]] as claimed in claim 1 or 2 any one of the preceding claims, characterized in that wherein each of the basalt fiber fabric (5), (7) is layers comprises a fabric made of yarn, tapes, strips or filaments of basalt.

- 7. (Currently Amended) The fire-resistant flexible wall [[(1)]] as claimed in claim 1 or 2, further including any one of the preceding claims, characterized in that it incorporates a flexible continuous metal layer [[(8)]].
- 8. (Currently Amended) The fire-resistant flexible wall [[(1)]] as claimed in claim 7, eharacterized in that wherein the first [[(5)]] or second [[(7)]] basalt fiber fabric layer and the flexible continuous metal layer [[(6)]] are joined together by means of an adhesive.
- 9. (Currently Amended) The fire-resistant flexible wall [[(1)]] as claimed in claim 8, characterized in that wherein the adhesive is sodium silicate-based.
  - 10. (Currently Amended) The fire-resistant flexible wall as claimed in any one of claims 7 9, characterized in that claim 7, wherein the flexible continuous metal layer (8) incorporates includes a metal or an alloy of metals selected from aluminum, titanium, and stainless steel.